

JET SPEED 2T

Synthetic performance two-stroke motor oil for the marine sector

Description

JET SPEED 2T is a high-performance two-stroke motor oil specially developed for jet ski engines and pleasure boats. Developed in accordance with the requirements of the marine sector. Guarantees low-smoke and low-odour combustion thanks to state-of-the-art additives.

Product features

- suitable for injection and pre-mix lubrication
- low-smoke combustion and minimal odour emissions
- very effective corrosion protection – even against salt water
- guarantees clean ignition plugs, pistons and piston rings
- no conglutination or coking of exhaust emissions
- absolute temperature stability
- suitable for engines with a catalytic converter

Field of application

For two-stroke jet skis and outboard motors of all performance classes. Suitable for injection lubrication as well as pre-mix lubrication.

Application

Mixing ratio in accordance with manufacturer's specifications or 1:50 to 1:100 (1–2%).

Notes

Not suitable for four-stroke engines or two-stroke diesel engines.

Specifications

API TC++, ASTM TSC-4, JASO FC, NMMA TC-W3

Technical Data

Properties	Test according to	Unit	Values
Colour			green
Density at 20 °C		g/cm ³	0.867
Viscosity at 40°C	DIN 51562-1	mm ² /s	48.7
Viscosity at 100°C	DIN 51562-1	mm ² /s	7.6
Viscosity index	DIN ISO 2909		123.0
Flash point	DIN EN ISO 2592	°C	>= 100
Pourpoint	ASTM D5950	°C	-36
TBN	DIN ISO 3771	mgKOH/g	3.90

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.