

FARMER UNI SAE 10W/40

Universal motor oil for four-stroke diesel and petrol engines

Description

MOTOREX FARMER UNI SAE 10W/40 is a versatile motor oil. High-quality base oils refined with modern additive technology guarantee reliable lubrication – even under the toughest conditions. FARMER UNI SAE 10W/40 offers outstanding corrosion protection and cleans the engine, thereby preventing damage caused by long-term storage.

Product features

- universal four-stroke petrol and diesel motor oil
- good viscosity-temperature behaviour
- low evaporation loss (NOACK)
- excellent engine cleanliness
- high level of wear protection
- good shear stability

Field of application

MOTOREX FARMER UNI SAE 10W/40 guarantees reliable operation in four-stroke petrol and diesel engines of agricultural machinery. With or without turbochargers. Ideal as a universal motor oil.

Specifications

ACEA A3/B4-16, ACEA E7-16, API CG-4, API CH-4, API CI-4, API SJ, API SL

Safety & Performance

CATERPILLAR ECF-1-A, MB 228.3 -> DTFR 15B110, GLOBAL DHD-1, MAN M3275-1, MB 229.1, MTU TYPE 2, VOLVO VDS-3

Technical Data

Properties	Test according to	Unit	Values
Density at 20 °C		g/cm ³	0.869
Viscosity at 40°C	DIN 51562-1	mm ² /s	95.6
Viscosity at 100°C	DIN 51562-1	mm ² /s	14.3
Viscosity index	DIN ISO 2909		154.0
Visco. according HTHS at 150°C	CEC-L-36 A-97	mPa.s	>= 3.5
Flash point	DIN EN ISO 2592	°C	> 200
Pourpoint	ASTM D5950	°C	-39
NOACK	CEC L-40-A-93	%	11.40
Sulphate residue content	DIN EN ISO 6245	%	1.50
TBN	DIN ISO 3771	mg KOH/g	10.70

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.