

# FORMULA 4T SAE 15W/50 MA2

High-quality synthetic motor oil for four-stroke motorbikes

## Description

High-quality synthetic blend motor oil for four-stroke motorbikes. This oil offers a very good level of protection for engines, gears and clutches in all fields. JASO MA2 approval guarantees the fault-free functioning of wet multi-disc clutches.

## Product features

- high level of wear protection
- absolute lubrication reliability
- stable at any temperature

## Field of application

Available in various viscosities, FORMULA 4T was specially developed for use in motorbike engines. Ideal for motorbikes with wet multi-disc clutches. Fulfils the manufacturer's requirements with regard to all specifications.

## Specifications

API SG, API SH, API SJ, API SL, JASO MA2



## Technical Data

Properties	Test according to	Unit	Values
Colour			yellowish-brown
Viscosity			SAE 15W/50
Density at 20 °C		g/cm <sup>3</sup>	0.870
Viscosity at 40°C	DIN 51562-1	mm <sup>2</sup> /s	120.2
Viscosity at 100°C	DIN 51562-1	mm <sup>2</sup> /s	16.9
Viscosity index	DIN ISO 2909		154.0
Visco. according HTHS at 150°C	CEC-L-36 A-97	mPa.s	>= 3.5
Flash point	DIN EN ISO 2592	°C	>= 200
Pourpoint	ASTM D5950	°C	-36
NOACK	CEC L-40-A-93	%	8.00
Sulphate residue content	DIN EN ISO 6245	%	0.80
TBN	DIN ISO 3771	mg KOH/g	5.70