

# ATF DEXRON III

Versatile gear oil for automatic gearboxes, meets requirements of DEXRON III H

## Description

ATF DEXRON III is a versatile, high-performance, latest-generation ATF, which meets the high requirements of the General Motors DEXRON III H specification. Improved cold properties and improved shifting performance compared to DEXRON II. Approved by a wide variety of manufacturers.

## Advantages

- protection against wear and corrosion
- high shear stability
- excellent low-temperature properties
- excellent ageing behaviour
- high thermal stability
- excellent shifting properties
- broad application spectrum

## Field of application

ATF DEXRON III can be used in cars, commercial vehicles, construction machinery and boats. The product has a wide range of applications in automatic gearboxes both with and without torque converter, for power steering, in gears or, depending on manufacturer, in hydraulic systems.

## Notes

Please adhere to the manufacturer's instructions.

## Specifications

DEXRON III H; ALLISON C4; CATERPILLAR TO-2.; MERCON; VOITH H55.6335.xx; ZF TE-ML-05L; ZF TE-ML-21L

## Safety + Performance

LT 71141; MB 236.1; MB 236.6; MB 236.7; MB 236.10; MB 236.11; VW TL 521 62; VW TL 529 90; ZF TE-ML-03D; ZF TE-ML-04D; ZF TE-ML-09; ZF TE-ML-11A; ZF TE-ML-11B; ZF TE-ML-14A; ZF TE-ML-17C

## Technical data

Properties	Unit	Test according to	Values
Colour			red
Density at 20 °C	g/cm <sup>3</sup>	ASTM D4052	0.857
Viscosity at 40 °C	mm <sup>2</sup> /s	DIN 51562-1	36.5
Viscosity at 100 °C	mm <sup>2</sup> /s	DIN 51562-1	7.5
Viscosity index		DIN ISO 2909	180
Pourpoint	°C	ASTM D5950	-51
Flash point C.O.C.	°C	DIN EN ISO 2592	>200
Brookfield	mPa·s	ASTM D 2983	-40 / 18900

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.

