

MOTO GEAR OIL SAE 10W/30

Multigrade gear oil for motorbikes

Description

MOTO GEAR OIL SAE 10W/30 is a multigrade, synthetic-base gear oil specially tailored to the requirements of motorbikes. First-class base oils and cutting-edge additives ensure optimum lubrication and shiftability.

Product features

- excellent shiftability at all temperatures
- first-class corrosion protection
- markedly powerful foam inhibition
- optimum lubricating reliability throughout the period of use

Field of application

MOTO GEAR OIL SAE 10W/30 is especially suitable for gears of two-stroke motorbikes equipped with wet clutches as well as for all motorbikes with separate gear lubrication.

Notes

Synthetic Performance

Specifications

API GL-4

Technical Data

Properties	Test according to	Unit	Values
Colour			brown
Viscosity			SAE 10W/30
Density at 20 °C		g/cm ³	0.874
Viscosity at 40°C	DIN 51562-1	mm ² /s	76.0
Viscosity at 100°C	DIN 51562-1	mm ² /s	11.7
Viscosity index	DIN ISO 2909		148.0
Flash point	DIN EN ISO 2592	°C	>= 200
Pourpoint	ASTM D5950	°C	-30

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.

MOTOREX USA Inc.

993 Federal Road
Brookfield, CT06804-1108, United States
Tel. +1 203-775-1291
motorex.com
27.03.2025 / 07

MOTOREX AG

Bern-Zürich-Strasse 31
4901 Langenthal, Schweiz
Tel. +41 62 919 75 75
motorex.com