

PRINOTH



MOTOREX
Oil of Switzerland

| | Husky | Everest | Leitwolf | New / T4F Leitwolf | | Bison | Beast | Version 2025_04/giss | | |
|---|-----------|----------|----------|-----------------------|-----------|---------------|-------------|---|---------|---|
| | Mercedes | Mercedes | MAN | MTU | Mercedes | Caterpillar | Caterpillar | | | |
| Diesel engine | 16-18 lt. | 34 lt. | 33 lt. | 37 lt. | 37-39 lt. | 32-33 lt. | 34 lt. | | | |
| normal interval * longer interval ● SCR + DPF □ | * | | * | * | | * | | UNIVERSAL SAE 10W/40 | | |
| | ● | | * | ● | | * | | POWER LD SAE 10W/40 | | |
| | ● / □ | | * / □ | ● / □ | | * / □ | | FOCUS QTM SAE 10W/40 | | |
| | ● / □ | | * / □ | ● / □ | | * / □ | | FOCUS QTM SAE 10W/30 | | |
| | ● / □ | | * / □ | ● / □ | | * / □ | | ALPINE EXTREME SAE 5W/30 | | |
| Cooling < 4.2011 | 28-36 lt. | 55 lt. | 50 lt. | 55 lt. | | 37-45 lt. | 37 lt. | COOLANT M5.0 do not mix with other coolants | | |
| Cooling > 5.2011 | | | | | | | | COOLANT M4.0 do not mix with other coolants | | |
| Hydraulic | 55-60 lt. | 110 lt. | 120 lt. | 140 lt. | | 82-130 lt. | 136 lt. | ALPINE MOTION HV 46 POOL ATF III | | |
| Hydraulic Bio | | | | | | | | ECOSYNT PAO 46 ECOSYNT HEES 46 (not mixed) | | |
| Hydraulic Cabin | 2 lt. | 2 lt. | 2 lt. | 3 lt. | | 2 lt. | | Same hydraulic oil as in the system | | |
| Hydraulic Bio Cabin | | | | | | | | | | |
| Splitter Box | 1,9 lt. | | 3,3 lt. | | | 3-3,2 lt. | 4,0 lt. | ALPINE PRO ISO VG 220 PENTA SAE 75W/140 GEAR SINTEC CLP ISO 220 | | |
| Striebel | | | | | | | | | 4,4 lt. | |
| Brevini | | 4,5 lt. | | | | | | | | |
| Ch.Schäfer | | 3,5 lt. | | | | | | | 1,5 lt. | |
| Wheel drive each | 1,4 lt. | | 1,6 lt. | | | 2-3.6 lt. | 2,0 lt. | | | |
| Lohmann | | 1,6 lt. | | | | | | | | |
| Brevini | | 4,0 lt. | | | | | | | | |
| Spindlehead Winch | | | | | | Winch gearbox | | | 1,6 lt. | ALPINE PRO ISO VG 220 PENTA SAE 75W/140 GEAR SINTEC CLP ISO 220 |
| Oil-lubricated bearings | | | | | | | | | | |
| Drum Winch | | | | | | Winch gearbox | | | 8 lt. | |
| Rope reel | | | | | | | | 1,6 lt. | | |
| SHERPA Winch | | | | | | Winch gearbox | | 2,5 lt. | | |
| AUTOMATIC Winch | | | | | | Winch gearbox | | 3 lt. | | |
| Cable guide roll / Sprocket | | | | | | | | FETT 5300 | | |
| Hydraulic Winch | | | | | | 10 lt. | | Same hydraulic oil as in the system | | |
| Cable guide roll / Sprocket | | | | | | 0,2-0,75 lt. | | | | |
| Curved teeth coupling | | | | | | 2x 150 gr. | | FETT 5300 | | |
| Splined shafts | | | | | | X | | COPPER PASTE | | |
| Wheel hubs / swinging arms | | | | | | X | | FETT 2000 FETT 3000 | | |
| Other lubrication points | | | | | | X | | | | |
| Battery terminals | | | | | | X | | ACCU PROTECT | | |
| AdBlue® | | | | | | 27-40 lt. | | AdBlue® | | |

DRIVEN BY HIGH PERFORMANCE

ALPINE LINE

All of the lubrication requirements associated with the Alpine infrastructure are covered by the extremely wide-ranging Alpine Line product portfolio. All of the products required for lubrication operation and maintenance are coordinated with one another and are available from a single source. This not only contributes to efficient procurement and significantly simplifies logistics but also promotes the responsible use of natural resources. Our products are designed to protect the environment and utilise biodegradable ingredients to promote harmony with nature. Central to this approach are expert support and advice, along with our analysis service. MOTOREX customers can rely on these strengths when it comes to finding sustainable solutions for their lubrication needs.



morex.com