

| | Paana | 100 | | 120-280 | 300 | 400 | 600 | | 600E+ | 800 | Version 2023.2/mda | |
|---------------------------------------------------------------|---------|------------|----------|-----------|------------|------------|----------------|--------------|-----------|--------|---------------------------------------------------------------|---------------------------------------------------------------------------|
| | Cummins | MB | Cummins | div. | div. | Cummins | MB | Cummins | MB | MAN | | |
| Diesel engine | 11 lt. | ~15 lt. | 20 lt. | 9 - 23lt. | 26-39 lt. | 21 lt. | 39,6 lt. | 30 lt. | 39,6 lt. | 45 lt. | | |
| short / normal interval * longer interval ● SCR + DPF □ | * | * | / | * | * | * | * | / | / | / | UNIVERSAL SAE 10W/40 | |
| | * | * / ● | * | * / ● | ● | * | ● | / | ● | / | POWER LD SAE 10W/40 | |
| | * / □ | * / ● / □ | / | * / ● | * / ● / □ | * | * / ● / □ | / | * / ● / □ | * / □ | FOCUS QTM SAE 10W/40 | |
| | * / □ | * / ● / □ | * / □ | * | * / ● / □ | * / □ | * / ● / □ | * / □ | * / ● / □ | * / □ | FOCUS QTM SAE 10W/30 | |
| | * / □ | * / ● / □ | * / □ | / | * / ● / □ | * / □ | * / ● / □ | * / □ | * / ● / □ | * / □ | ALPINE EXTREME SAE 5W/30 | |
| Cooling | 19 lt. | / | / | X | 33 lt. | 35 lt. | / | / | / | / | COOLANT M5.0 do not mix with other coolants | |
| Cooling >2015 (SCR) | | 25 lt. | 25,5 lt. | / | / | / | 36 lt. | 39 lt. | 36 lt. | 24 lt. | COOLANT M4.0 do not mix with other coolants | |
| Hydraulic | 70 lt. | 80 lt. | 100 lt. | X | 100 lt. | 80 lt. | 100 lt. | | 100 lt. | / | ALPINE MOTION HV 46 ALPINE ATF DEXRON III | |
| Hydraulic Bio | | | | | | | | | | | 120 lt. | ECOSYNT PAO 46 (instead of Syntofluid Extreme 50) |
| Wheel drive each | 0,8 lt. | 2,4/3,5lt. | / | X | / | / | / | / | / | / | GEAR SINTEC CLP ISO 150 ALPINE PRO 220 | |
| | | | | | | | | | | | 1,5 lt. | vary type |
| Splitter box | / | 1,8 lt. | 2,4 lt. | X | vary type | 1,8 lt. | 2,4 lt. | 2 lt. | 2,4 lt. | 2 lt. | | |
| Tillers gearbox | / | / | / | X | / | / | / | / | 1,3 lt. | / | | |
| Transformer oil | / | / | / | / | / | / | / | / | 60 lt. | / | Original fluid replaced with TRANSFORMATORENOEL SEV | |
| Winch | | | | | 3 t | 4 t | 4,5 t | 4,6 t | | | | |
| Winch gearbox | | | | | 10 lt. | 10 lt. | 9 lt. | | | | | ALPINE PRO 220 PENTA SAE 75W/140 GEAR SINTEC CLP ISO 220 |
| Windlass gear | | | | | 0,5 lt. | 0,5 lt. | 0,85 - 1,1 lt. | | | | | ALPINE PRO 220 UNISYNT ZX SAE 75W/90 GEAR SINTEC CLP ISO 220 |
| Slewing gear drive | | | | | 0,9 lt. | 0,9 lt. | 2x 1,7 lt. | | | | | |
| Winch brake | | | | | 0,08 lt. | 0,08 lt. | 0,08 lt. | | | | | FOCUS QTM, ALPINE EXTREME |
| Multi-plate clutch | | | | | 1,5 lt. | / | / | | | | | COREX HV 22 |
| Hand pump | | | | | / | / | 0,7 lt. | | | | | Hydraulic Fluid |
| Slewing-gear | | | | | X | X | X | | | | | SPRAY 1219 |
| Cable guide roll / Sprocket | | | | | X | X | X | | | | | FETT 5300 |
| Wheel hubs / swinging arms | | | | | | | | | | X | FETT 2000 | |
| Other lubrication points | | | | | | | | | | X | FETT 3000 | |
| Geared coupling | | | | | | | | | | X | FETT 5300 | |
| Splined shafts | | | | | | | | | | X | COPPER PASTE | |
| Servo adjustment device for Moog valves | | | | | | | | | | X | TRANSFORMATORENOEL SEV | |
| Battery terminals | | | | | | | | | | X | ACCU PROTECT | |
| AdBlue | | | | | | | | | | X | ADBLUE® | |