

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **FUEL STABILIZER**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Gasoline additive

Only for proper handling.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MOTOREX AG

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

Further information obtainable from: msds@motorex.com

1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Signal word *Danger*

Hazard-determining components of labelling:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
propan-2-ol

Hydrocarbons, C10, aromatics, >1% naphthalene

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

Trade name: FUEL STABILIZER

(Contd. of page 1)

- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P331 Do NOT induce vomiting.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

- Contains biocidal products: propan-2-ol

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances

- **Dangerous components:**

CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	≥25-≤70%
EC number: 926-141-6 Reg.nr.: 01-2119456620-43	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Asp. Tox. 1, H304, EUH066	25-50%
EC number: 919-284-0 Reg.nr.: 01-2119463588-24	Hydrocarbons, C10, aromatics, >1% naphthalene Carc. 2, H351; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066	≥1-<2.5%
CAS: 91-20-3 EINECS: 202-049-5 Index number: 601-052-00-2 Reg.nr.: 01-2119561346-37	naphthalene Flam. Sol. 2, H228; Carc. 2, H351; Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302	≥0.1-<0.25%

- **Regulation (EC) No 648/2004 on detergents / Labelling for contents**

aliphatic hydrocarbons	≥30%
------------------------	------

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately rinse with water.

- **After eye contact:**

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed**

- No further relevant information available.

(Contd. on page 3)

Trade name: FUEL STABILIZER

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
The recommended storage temperature is (deg.C): ≤50°C
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Trade name: **FUEL STABILIZER**

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
-----	--

· DNELs

67-63-0 propan-2-ol

Oral	DNEL/general population/Systemic effects/Long-term	26 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	888 mg/kg/24h (worker)
	DNEL/general population/Systemic effects/Long-term	319 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long-term	500 mg/m ³ (worker)
	DNEL/general population/Systemic effects/Long-term	89 mg/m ³ (consumer)

91-20-3 naphthalene

Dermal	DNEL / Workers / Systemic effects / Long-term	3.57 mg/kg/24h (worker)
Inhalative	DNEL / Workers / Systemic effects / Long-term	25 mg/m ³ (worker)
	DNEL / Workers / Local Effects / Long-term	25 mg/m ³ (worker)

· PNECs

67-63-0 propan-2-ol

Oral	PNEC / Predators / Secondary poisoning	160 mg/kg food (secondary poisoning (predators))
	PNEC / Aquatic organisms / Freshwater	140.9 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Marine water	140.9 mg/l (aquatic organisms)
	PNEC / Aquatic org / intermittent releases (freshwater)	140.9 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Sewage treatment plant / STP	2,251 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Sediment (freshwater)	552 mg/kg (aquatic organisms)
	PNEC / Aquatic organisms / Sediment (marine water)	552 mg/kg (aquatic organisms)
	PNEC / Terrestrial organism / Soil	28 mg/kg (terrestrial organisms)

91-20-3 naphthalene

	PNEC / Aquatic organisms / Freshwater	0.0024 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Marine water	0.0024 mg/l (Bioaccumulation)
	PNEC / Aquatic org / intermittent releases (freshwater)	0.02 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Sewage treatment plant / STP	2.9 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Sediment (freshwater)	0.0672 mg/kg (aquatic organisms)
	PNEC / Aquatic organisms / Sediment (marine water)	0.0672 mg/kg (aquatic organisms)
	PNEC / Terrestrial organism / Soil	0.0533 mg/kg (terrestrial organisms)

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

(Contd. on page 5)

Trade name: FUEL STABILIZER

(Contd. of page 4)

- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Hand protection**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection**



safety goggles

- **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Liquid
- **Colour:** Blue
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** Undetermined.
- **Flammability** Highly flammable.
- **Lower and upper explosion limit**
- **Lower:** Not determined.
- **Upper:** Not determined.
- **Flash point:** 17 °C
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity** Not determined.
- **Consistency**
- **Dynamic:** Not determined.
- **Solubility**
- **water:** Not miscible or difficult to mix.

(Contd. on page 6)

Trade name: FUEL STABILIZER

(Contd. of page 5)

<ul style="list-style-type: none"> · Partition coefficient n-octanol/water (log value) · Heat Capacity · Vapour pressure: · Density and/or relative density · Density at 20 °C: · Relative density · Vapour density 	<p>Not determined.</p> <p>Not determined.</p> <p>0.805 g/cm³ (ASTM D 4052)</p> <p>Not determined.</p> <p>Not determined.</p>
<ul style="list-style-type: none"> · 9.2 Other information · Appearance: · Form: · Important information on protection of health and environment, and on safety. · Explosive properties: · Solvent separation test: · VOC (EC) · Change in condition · Evaporation rate 	<p>Fluid</p> <p>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</p> <p>86.70 %</p> <p>Not determined.</p>
<ul style="list-style-type: none"> · Information with regard to physical hazard classes · Explosives · Flammable gases · Aerosols · Oxidising gases · Gases under pressure · Flammable liquids · Flammable solids · Self-reactive substances and mixtures · Pyrophoric liquids · Pyrophoric solids · Self-heating substances and mixtures · Substances and mixtures, which emit flammable gases in contact with water · Oxidising liquids · Oxidising solids · Organic peroxides · Corrosive to metals · Desensitised explosives 	<p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Highly flammable liquid and vapour.</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p>

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 7)

Trade name: FUEL STABILIZER

(Contd. of page 6)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

67-63-0 propan-2-ol

Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	16.4 ml/kg (rabbit)
	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50 / 6h	10,000 ppm (rat)
	NOAEC	5,000 ppm (rat)
	NOEC	500-5,000 ppm (rat)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Oral	LD50	5,000-15,000 mg/kg (rat)
	NOAEL	1,000-5,000 mg/kg/24h (rat)
Dermal	LD50	2,000 mg/kg (rat)
	NOAEL	200 ppm (rat)
Inhalative	LC50 / 4h	4.951-6.1 mg/l (rat) (OECD 403)
	NOAEL	200 ppm (rat)
	NOAEC	275-10,400 mg/m3 (rat)

91-20-3 naphthalene

Oral	LD50	533-710 mg/kg (mouse)
	NOEL	100 mg/kg/24h (rat)
	NOAEL	100-200 mg/kg/24h (mouse) 200 mg/kg/24h (rat)
Dermal	LOAEL	400 mg/kg/24h (rat)
	LD50	2,500-16,000 mg/kg (rat)
	NOEL	300 mg/kg/24h (rat)
Inhalative	NOAEL	1,000 mg/kg/24h (rat)
	LC0 / 4h	77.7 ppm (rat)
	LC50 / 4h	77.7 ppm (rat)
	LC50 / 4h	400 mg/m3 (rat)
	NOAEL	300 mg/m3 (rat)
	NOAEC	1 ppm (rat)
	LOAEC	2-10 ppm (rat)
	LOAEC	11 mg/m3 (rat)
	NOEC	0.1 ppm (rat)

- **Primary irritant effect:**
- **Serious eye damage/irritation** Causes serious eye irritation.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **Aspiration hazard** May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

GB

(Contd. on page 8)

Trade name: **FUEL STABILIZER**

(Contd. of page 7)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

67-63-0 propan-2-ol

LC50	9.64-10 mg/l/96h (fish)
LC50	10,000 mg/l/24h (aquatic invertebrates)
EC50	10,000 mg/l/24h (aquatic invertebrates)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

LL50	2-5 mg/l/96h (fish)
LL50	2-5 mg/l/48h (fish)
LL50	5-17 mg/l/24h (fish)
EL50	1.4 mg/l/48h (aquatic invertebrates)
EL50	4.6 mg/l/24h (aquatic invertebrates)
	1-3 mg/l/24h (algae / cyanobacteria)
EL50	1-3 mg/l/72h (algae / cyanobacteria)
EL50	0.81-0.89 mg/l/21d (aquatic invertebrates)
NOELR	1.22 mg/l/21d (aquatic invertebrates)
NOELR	1,000 mg/l/72h (algae / cyanobacteria)

91-20-3 naphthalene

LC50	1.6-7.9 mg/l/96h (fish)
LC50	6.35 mg/l/48h (fish)
LC50	6.08 mg/l/72h (fish)
LC50	2.4-7.76 mg/l/24h (fish)
EC50	0.4-0.5 mg/l/72h (algae / cyanobacteria)
EC50	2.16 mg/l/48h (aquatic invertebrates)

· **12.2 Persistence and degradability** No further relevant information available.

· 12.3 Bioaccumulative potential

67-63-0 propan-2-ol

Partition coefficient	0.05 [---] (log Kow) (Bioaccumulation)
Biodegradability	>70 % (28d) (Biodegradability) (EU Method C.5)

91-20-3 naphthalene

Partition coefficient	3.4 [---] (log Kow) (Bioaccumulation)
Biodegradability	>74 % (28d) (Biodegradability) (OECD 301 C)

· **12.4 Mobility in soil** No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes:

Water hazard class 2 (according to Appendix 1 AWSV): significantly hazardous to water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

GB

(Contd. on page 9)

Trade name: FUEL STABILIZER

(Contd. of page 8)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

· **Uncleaned packaging:**

· **Recommendation:**

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR/RID/ADN, IMDG, IATA**

UN1219

· **14.2 UN proper shipping name**

· **ADR/RID/ADN**

1219 ISOPROPANOL (ISOPROPYL ALCOHOL)

· **IMDG, IATA**

ISOPROPANOL (ISOPROPYL ALCOHOL)

· **14.3 Transport hazard class(es)**

· **ADR/RID/ADN**



· **Class**

3 (F1) Flammable liquids.

· **Label**

3

· **IMDG, IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

· **14.4 Packing group**

· **ADR/RID/ADN, IMDG, IATA**

II

· **14.5 Environmental hazards:**

Not applicable.

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):** 33

· **EMS Number:**

F-E,S-D

· **Stowage Category**

B

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **ADR/RID/ADN**

· **Limited quantities (LQ)**

1L

(Contd. on page 10)

Trade name: FUEL STABILIZER

(Contd. of page 9)

· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
<hr/>	
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· Regulated explosives precursors
None of the ingredients is listed.

· Regulated poisons
None of the ingredients is listed.

· Reportable explosives precursors
None of the ingredients is listed.

· Reportable poisons
None of the ingredients is listed.

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c** FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008. No special training instructions to ensure protection of human health and environment are required.

- **purity requirement**
- **Relevant phrases**

H225	Highly flammable liquid and vapour.
H228	Flammable solid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

(Contd. on page 11)

Trade name: FUEL STABILIZER

(Contd. of page 10)

EUH066 Repeated exposure may cause skin dryness or cracking.

- **Department issuing SDS:** Abteilung Produktsicherheit
- **Abbreviations and acronyms:**
 - Flam. Liq. 2: Flammable liquids – Category 2*
 - Flam. Sol. 2: Flammable solids – Category 2*
 - Acute Tox. 4: Acute toxicity – Category 4*
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*
 - Carc. 2: Carcinogenicity – Category 2*
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*
 - Asp. Tox. 1: Aspiration hazard – Category 1*
 - Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1*
 - Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*
- *** Data compared to the previous version altered.**

Annex: Exposure scenario 1

- **Short title of the exposure scenario** Industrial use of additives
- **Sector of Use**
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites*
- **Product category** PC14 Metal surface treatment products
- **Process category**
 - PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.*
 - PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions*
 - PROC18 General greasing /lubrication at high kinetic energy conditions*
 - PROC20 Use of functional fluids in small devices*
- **Environmental release category**
 - ERC7 Use of functional fluid at industrial site*
 - ERC9a Widespread use of functional fluid (indoor)*
 - ERC9b Widespread use of functional fluid (outdoor)*
- **Description of the activities / processes covered in the Exposure Scenario**
 - See section 1 of the annex to the Safety Data Sheet.*
- **Conditions of use**
 - **Duration and frequency** 5 workdays/week.
 - **Physical parameters**
 - **Physical state** Fluid
 - **Concentration of the substance in the mixture** The substance is main component.
 - **Other operational conditions**
 - **Other operational conditions affecting environmental exposure** No special measures required.
 - **Other operational conditions affecting consumer exposure** Not required.
 - **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** No special measures required.
- **Personal protective measures** No special measures required.
- **Measures for consumer protection** No special measures required.
- **Environmental protection measures**
 - **Air** No special measures required.
 - **Water** No special measures required.
 - **Disposal measures** Ensure that waste is collected and contained.
 - **Disposal procedures** Dispose of product residues with household waste.
 - **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.

(Contd. on page 12)

Trade name: FUEL STABILIZER

(Contd. of page 11)

· **Guidance for downstream users** No further relevant information available.

Annex: Exposure scenario 2

- **Short title of the exposure scenario** Professional use of additives
- **Sector of Use**
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC14 Metal surface treatment products
- **Process category**
PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC18 General greasing /lubrication at high kinetic energy conditions
PROC20 Use of functional fluids in small devices
- **Environmental release category**
ERC9a Widespread use of functional fluid (indoor)
ERC9b Widespread use of functional fluid (outdoor)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting consumer exposure** Not required.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** No special measures required.
- **Personal protective measures** No special measures required.
- **Measures for consumer protection** No special measures required.
- **Environmental protection measures**
- **Air** No special measures required.
- **Water** No special measures required.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures** Dispose of product residues with household waste.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

Annex: Exposure scenario 3

- **Short title of the exposure scenario** Private use of additives
- **Sector of Use** SU21 Consumer uses: Private households / general public / consumers
- **Product category** PC14 Metal surface treatment products
- **Process category**
PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

(Contd. on page 13)

Trade name: FUEL STABILIZER

(Contd. of page 12)

PROC18 General greasing /lubrication at high kinetic energy conditions

PROC20 Use of functional fluids in small devices

· **Environmental release category**

ERC9a Widespread use of functional fluid (indoor)

ERC9b Widespread use of functional fluid (outdoor)

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use**

· **Duration and frequency** 5 workdays/week.

· **Physical parameters**

· **Physical state** Fluid

· **Concentration of the substance in the mixture** The substance is main component.

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure** No special measures required.

· **Other operational conditions affecting consumer exposure** Not required.

· **Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures** No special measures required.

· **Technical protective measures** No special measures required.

· **Personal protective measures** No special measures required.

· **Measures for consumer protection** No special measures required.

· **Environmental protection measures**

· **Air** No special measures required.

· **Water** No special measures required.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures** Dispose of product residues with household waste.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer** Not relevant for this Exposure Scenario.

· **Guidance for downstream users** No further relevant information available.