

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **CONCEPT TS-X SAE 5W30**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Only for proper handling.

Engine oil

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MOTOREX AG
Bern-Zürich-Strasse 31, Postfach
CH-4901 Langenthal
Tel. +41 (0)62 919 75 75
www.motorex.com

Further information obtainable from: msds@motorex.com

1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Additional information:

Contains C14-16-18 Alkyl Phenol. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 72623-87-1 EINECS: 276-738-4 Index number: 649-483-00-5 Reg.nr.: 01-2119474889-13	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Asp. Tox. 1, H304	≥70-≤90%
CAS: 64742-54-7 EINECS: 265-157-1 Index number: 649-467-00-8 Reg.nr.: 01-2119484627-25	Distillates (petroleum), hydrotreated heavy paraffinic Asp. Tox. 1, H304	≥1-≤7.5%
CAS: 72623-86-0 EINECS: 276-737-9 Index number: 649-482-00-X Reg.nr.: 01-2119474878-16	Lubricating oils, C15-30, hydrotreated neutral oil-based Asp. Tox. 1, H304	≥1-≤2.5%

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 15.05.2023

Version number 1.1 (replaces version 1.0)

Revision: 15.05.2023

Trade name: CONCEPT TS-X SAE 5W30

(Contd. of page 1)

CAS: 64742-56-9 EINECS: 265-159-2 Index number: 649-469-00-9 Reg.nr.: 01-2119480132-48	Distillates (petroleum), solvent-dewaxed light paraffinic Asp. Tox. 1, H304	≥0.1-≤2.5%
CAS: 64742-65-0 EINECS: 265-169-7 Index number: 649-474-00-6 Reg.nr.: 01-2119471299-27	Distillates (petroleum), solvent-dewaxed heavy paraffinic Asp. Tox. 1, H304	≥0.1-≤2.5%
CAS: 64742-70-7 EINECS: 265-174-4 Index number: 649-477-00-2	Paraffin oils (petroleum), catalytic dewaxed heavy Asp. Tox. 1, H304	≥0.1-≤2.5%
EC number: 931-468-2	C14-16-18 Alkyl Phenol STOT RE 2, H373; Skin Sens. 1, H317	0.1-0.25%

Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346.
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 15.05.2023

Version number 1.1 (replaces version 1.0)

Revision: 15.05.2023

Trade name: **CONCEPT TS-X SAE 5W30**

(Contd. of page 2)

- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
The recommended storage temperature is (deg.C): ≤50°C
- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **DNELs**

72623-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based		
Inhalative	DNEL / Workers / Local Effects / Long-term	5.4 mg/m ³ /8h (worker)
	DNEL/general population/Local effects/Long-term	1.2 mg/m ³ /24h (consumer)
72623-86-0 Lubricating oils, C15-30, hydrotreated neutral oil-based		
Inhalative	DNEL / Workers / Local Effects / Long-term	5.4 mg/m ³ /8h (worker)
	DNEL/general population/Local effects/Long-term	1.2 mg/m ³ /24h (consumer)
64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic		
Dermal	DNEL / Workers / Systemic Effects / Long-term	1 mg/kg/8h (worker)
Inhalative	DNEL / Workers / Systemic Effects / Long-term	2.7 mg/m ³ /8h (worker)
64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic		
Inhalative	DNEL	5.4 mg/m ³ /8h (worker)
	DNEL	1.2 mg/m ³ /24h (consumer)

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**
Not necessary if room is well-ventilated.
Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.
- **Hand protection**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Trade name: CONCEPT TS-X SAE 5W30

(Contd. of page 3)

- **Eye/face protection** Goggles recommended during refilling
- **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

- **General Information**
- **Physical state** Fluid
- **Colour:** Yellow-brown
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** Undetermined.
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** Not determined.
- **Upper:** Not determined.
- **Flash point:** >200 °C
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity** 55.7 mm²/s @ 40 °C
- **Consistency**
- **Dynamic:** Not determined.
- **Solubility**
- **water:** Not miscible or difficult to mix.
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Heat Capacity**
- **Vapour pressure:** Not determined.
- **Vapour pressure:**
- **Density and/or relative density**
- **Density at 20 °C:** 0.852 g/cm³ (ASTM D 4052)
- **Relative density** Not determined.
- **Vapour density** Not determined.

· 9.2 Other information

- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Explosive properties:** Product does not present an explosion hazard.
- **Solvent separation test:**
- **VOC (EC)** 0.00 %
- **Change in condition**
- **Evaporation rate** Not determined.

· Information with regard to physical hazard classes

- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 15.05.2023

Version number 1.1 (replaces version 1.0)

Revision: 15.05.2023

Trade name: **CONCEPT TS-X SAE 5W30**

(Contd. of page 4)

· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

72623-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
Inhalative		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOAEC	980 mg/m3 (rat)
	NOEC	220 mg/m3 (rat)

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
Inhalative		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 15.05.2023

Version number 1.1 (replaces version 1.0)

Revision: 15.05.2023

Trade name: CONCEPT TS-X SAE 5W30

(Contd. of page 5)

	NOAEL	980 mg/m ³ (rat)
72623-86-0 Lubricating oils, C15-30, hydrotreated neutral oil-based		
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
Inhalative	LOAEL	100 mg/kg/24h (mouse)
	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m ³ (rat)
	NOAEL	980 mg/m ³ (rat)
64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic		
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
Inhalative	LOAEL	100 mg/kg/24h (mouse)
	NOEL	220 mg/m ³ (rat)
	NOAEL	980 mg/m ³ (rat)
64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic		
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
Inhalative	LOAEL	100 mg/kg/24h (mouse)
	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m ³ (rat)
	NOAEL	980 mg/m ³ (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

GB

(Contd. on page 7)

Trade name: **CONCEPT TS-X SAE 5W30**

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

72623-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

LL50 10,000 mg/l/96h (aquatic invertebrates)
100 mg/l/96h (fish)

LL50 10,000 mg/l/72h (aquatic invertebrates)

LL50 10,000 mg/l/48h (aquatic invertebrates)

LL50 10,000 mg/l/24h (aquatic invertebrates)

EL50 10,000 mg/l/48h (aquatic invertebrates)

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

LL50 10,000 mg/l/96h (aquatic invertebrates)
100 mg/l/96h (fish)

LL50 10,000 mg/l/72h (aquatic invertebrates)

LL50 10,000 mg/l/48h (aquatic invertebrates)

LL50 10,000 mg/l/24h (aquatic invertebrates)

EL50 10,000 mg/l/48h (aquatic invertebrates)

72623-86-0 Lubricating oils, C15-30, hydrotreated neutral oil-based

LL50 10,000 mg/l/96h (aquatic invertebrates)
100 mg/l/96h (fish)

LL50 10,000 mg/l/72h (aquatic invertebrates)

LL50 10,000 mg/l/48h (aquatic invertebrates)

LL50 10,000 mg/l/24h (aquatic invertebrates)

EL50 10,000 mg/l/48h (aquatic invertebrates)

64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic

LL50 10,000 mg/l/96h (aquatic invertebrates)
100 mg/l/96h (fish)

LL50 10,000 mg/l/72h (aquatic invertebrates)

LL50 10,000 mg/l/48h (aquatic invertebrates)

LL50 10,000 mg/l/24h (aquatic invertebrates)

EL50 10,000 mg/l/48h (aquatic invertebrates)

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic

LL50 10,000 mg/l/96h (aquatic invertebrates)
100 mg/l/96h (fish)

LL50 10,000 mg/l/72h (aquatic invertebrates)

LL50 10,000 mg/l/48h (aquatic invertebrates)

LL50 10,000 mg/l/24h (aquatic invertebrates)

EL50 10,000 mg/l/48h (aquatic invertebrates)

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

Partition coefficient >6 [---] (log Kow) (Bioaccumulation)

72623-86-0 Lubricating oils, C15-30, hydrotreated neutral oil-based

Partition coefficient >6 [---] (log Kow) (Bioaccumulation)

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 15.05.2023

Version number 1.1 (replaces version 1.0)

Revision: 15.05.2023

Trade name: **CONCEPT TS-X SAE 5W30**

(Contd. of page 7)

64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic

Partition coefficient >3.5 [---] (log Kow) (Bioaccumulation)

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic

Partition coefficient >6 [---] (log Kow) (Bioaccumulation)

- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Contact waste processors for recycling information.
Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|-----------------|
| · 14.1 UN number or ID number | Void |
| · ADR/RID/ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name | Void |
| · ADR/RID/ADN, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es) | Void |
| · ADR/RID/ADN, ADN, IMDG, IATA | Void |
| · Class | Void |
| · 14.4 Packing group | Void |
| · ADR/RID/ADN, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · UN "Model Regulation": | Void |

GB

(Contd. on page 9)

Trade name: CONCEPT TS-X SAE 5W30

(Contd. of page 8)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- **purity requirement**
- **Relevant phrases**
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H373 May cause damage to organs through prolonged or repeated exposure.
- **Department issuing SDS:** Abteilung Produktsicherheit
- **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Sens. 1: Skin sensitisation – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
- *** Data compared to the previous version altered.**

Annex: Exposure scenario 1

- **Short title of the exposure scenario**
Industrial use of lubricants and greases in vehicles or machinery
- **Sector of Use**
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category**
PC16 Heat transfer fluids
PC17 Hydraulic fluids
PC24 Lubricants, greases, release products
- **Process category**
PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

(Contd. on page 10)

Trade name: CONCEPT TS-X SAE 5W30

(Contd. of page 9)

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

· **Environmental release category**

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC7 Use of functional fluid at industrial site

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use**

· **Duration and frequency** 5 workdays/week.

· **Physical parameters**

· **Physical state** Fluid

· **Concentration of the substance in the mixture** The substance is main component.

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure** No special measures required.

· **Other operational conditions affecting consumer exposure** Not required.

· **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures** No special measures required.

· **Technical protective measures** No special measures required.

· **Personal protective measures** No special measures required.

· **Measures for consumer protection** No special measures required.

· **Environmental protection measures**

· **Air** No special measures required.

· **Water** No special measures required.

· **Disposal measures**

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

· **Disposal procedures** Dispose of product residues with household waste.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer** Not relevant for this Exposure Scenario.

· **Guidance for downstream users** No further relevant information available.

Annex: Exposure scenario 2

· **Short title of the exposure scenario**

Professional use of lubricants and greases in vehicles or machines

· **Sector of Use**

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category**

PC16 Heat transfer fluids

PC17 Hydraulic fluids

PC24 Lubricants, greases, release products

· **Process category**

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC20 Use of functional fluids in small devices

· **Environmental release category**

ERC9a Widespread use of functional fluid (indoor)

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 15.05.2023

Version number 1.1 (replaces version 1.0)

Revision: 15.05.2023

Trade name: CONCEPT TS-X SAE 5W30

(Contd. of page 10)

- ERC9b Widespread use of functional fluid (outdoor)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting consumer exposure** Not required.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** No special measures required.
- **Personal protective measures** No special measures required.
- **Measures for consumer protection** No special measures required.
- **Environmental protection measures**
- **Air** No special measures required.
- **Water** No special measures required.
- **Disposal measures**
Disposal must be made according to official regulations.
Ensure that waste is collected and contained.
- **Disposal procedures** Dispose of product residues with household waste.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

Annex: Exposure scenario 3

- **Short title of the exposure scenario** Private use of lubricants and greases in vehicles or machines
- **Sector of Use** SU21 Consumer uses: Private households / general public / consumers
- **Product category** PC24 Lubricants, greases, release products
- **Environmental release category**
- ERC9a Widespread use of functional fluid (indoor)
- ERC9b Widespread use of functional fluid (outdoor)
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting consumer exposure** Not required.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** No special measures required.
- **Personal protective measures** No special measures required.
- **Measures for consumer protection** No special measures required.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 15.05.2023

Version number 1.1 (replaces version 1.0)

Revision: 15.05.2023

Trade name: CONCEPT TS-X SAE 5W30

(Contd. of page 11)

- **Environmental protection measures**
- **Air** No special measures required.
- **Water** No special measures required.
- **Disposal measures**
Disposal must be made according to official regulations.
Ensure that waste is collected and contained.
- **Disposal procedures** Dispose of product residues with household waste.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

GB