


1 Identification

- **Product identifier**
- **Trade name: CROSS POWER 2T**
- **Application of the substance / the mixture**
Only for proper handling.
Engine oil
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MOTOREX AG
Bern-Zürich-Strasse 31, Postfach
CH-4901 Langenthal
Tel. +41 (0)62 919 75 75
www.motorex.com
- **Information department: msds@motorex.com**
- **Emergency telephone number:**
USA + Kanada: 1 800 424 9300 (Chemtrec Chemical Manufacturers Association, Arlington, VA 22209)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Sensitization - Skin 1 H317 May cause an allergic skin reaction.

 - **Label elements**
 - **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
 - **Hazard pictograms**
- 

GHS07
- **Signal word** Warning
 - **Hazard-determining components of labeling:**
Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts
 - **Hazard statements**
H317 May cause an allergic skin reaction.
 - **Precautionary statements**
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves.
P302+P352 If on skin: Wash with plenty of water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
 - **Classification system:**
 - **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 1
Reactivity = 0

(Contd. on page 2)

Printing date 12/19/2023

Reviewed on 12/19/2023

Trade name: **CROSS POWER 2T**

(Contd. of page 1)

- **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 1000172-11-1 EC number: 700-184-9	Pentadecane, 7-methylene mixed with 1-tetradecene, dimers and trimers, hydrogenated Aspiration Hazard 1, H304	10-25%
EC number: 926-141-6	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Aspiration Hazard 1, H304; Flammable Liquids 4, H227	10-25%
CAS: 722503-68-6 EC number: 682-816-2	Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts Sensitization - Skin 1, H317	≥0.25-<1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Remove residues with soap and water.
Remove contaminated clothing immediately.
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water.
Consult a physician if irritation develops.
- **After swallowing:**
Do not induce vomiting. Do not take in resorption stimulating agents.
Consult a physician who will decide on need and method of emptying the stomach.
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
In case of fire carbon, sulphur and nitrogen oxides can be formed.

(Contd. on page 3)

Trade name: CROSS POWER 2T

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Protective Action Criteria for Chemicals**

· PAC-1:

1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm

· PAC-2:

1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm

· PAC-3:

1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm

- **Reference to other sections**
No dangerous substances are released.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**
Vapours of this product are heavier than air and will collect in low areas such as pits, storage tanks, and other confined areas.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
The recommended storage temperature is (deg.C): ≤50°C
Store containers closed and protect against rain, dust, heat and other atmospheric influences.
Store in cool, dry well ventilated area away from sources of ignition and heat.
- **Storage class:** 10
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

Trade name: CROSS POWER 2T

(Contd. of page 3)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Additional information about design of technical systems:** No further data; see section 7.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Not necessary if room is well-ventilated.
Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.
- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- | | |
|---|---|
| · Color: | Red |
| · Odor: | Characteristic |
| · Odor threshold: | Not determined. |
| · Melting point/Melting range: | Undetermined. |
| · Boiling point/Boiling range: | Undetermined. |
| · Flammability (solid, gaseous): | Not applicable. |
| · Explosion limits: | |
| · Lower: | 0.6 Vol. % |
| · Upper: | 6.5 Vol. % |
| · Flash point: | 110 °C (230 °F) |
| · Auto igniting: | >200 °C (DIN 51794) |
| · Decomposition temperature: | Not determined. |
| · pH-value: | Not determined. |
| · Viscosity: | |
| · Kinematic: | 56 mm ² /s @ 40 °C (132.8 mm ² /s @ 104 °F) |
| · Consistency | |
| · Dynamic: | Not determined. |

(Contd. on page 5)

Printing date 12/19/2023

Reviewed on 12/19/2023

Trade name: CROSS POWER 2T

(Contd. of page 4)

· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Vapor pressure:	Not determined.
· Vapor pressure:	
· Density at 20 °C (68 °F):	0.874 g/cm ³ (7.294 lbs/gal) (ASTM D 4052)
· Relative density	Not determined.
· Vapor density	Not determined.

· Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Danger of explosion:	Product does not present an explosion hazard.
· Solvent separation test	
· VOC content:	15.00 %
· VOC (EU)	15.01 %
· Change in condition	
· Solidification point:	-33 °C (-27.4 °F)
· Evaporation rate	Not determined.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Oral	LD50	5,000 mg/kg (rat)
	NOAEL	1,000-5,000 mg/kg/24h (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
	NOAEL	200 ppm (rat)
Inhalative	LC50 / 4h	5.28 mg/l (rat)
	NOAEL	200 ppm (rat)
	NOAEC	275-10,400 mg/m ³ (rat)

- **Sensitization:** May cause an allergic skin reaction.
- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

(Contd. on page 6)

US

Printing date 12/19/2023

Reviewed on 12/19/2023

Trade name: **CROSS POWER 2T**

(Contd. of page 5)

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

LL50	2-5 mg/l/96h (fish)
LL50	2-5 mg/l/48h (fish)
LL50	5-17 mg/l/24h (fish)
EL50	1.4 mg/l/48h (aquatic invertebrates)
EL50	4.6 mg/l/24h (aquatic invertebrates)
	1-3 mg/l/24h (algae / cyanobacteria)
EL50	1-3 mg/l/72h (algae / cyanobacteria)
EL50	0.81-0.89 mg/l/21d (aquatic invertebrates)
NOELR	1.22 mg/l/21d (aquatic invertebrates)
NOELR	1,000 mg/l/72h (algae / cyanobacteria)

- **Persistence and degradability** No further relevant information available.

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects**

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- **DOT, ADR/RID/ADN, ADN, IMDG, IATA** Void

(Contd. on page 7)

Trade name: CROSS POWER 2T

(Contd. of page 6)

- | | |
|--|-----------------|
| · UN proper shipping name | Void |
| · DOT, ADR/RID/ADN, ADN, IMDG, IATA | Void |
| · Transport hazard class(es) | Void |
| · DOT, ADR/RID/ADN, ADN, IMDG, IATA | Void |
| · Class | Void |
| · Packing group | Void |
| · DOT, ADR/RID/ADN, IMDG, IATA | Void |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Void |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
100-41-4	ethylbenzene

TSCA (Toxic Substances Control Act):

68334-05-4	Fatty acids, C18-unsatd., dimers, 2-ethylhexyl esters	ACTIVE
9003-29-6	Polybuten (Isobutylene-/Buten-Copolymer)	ACTIVE
1000172-11-1	Pentadecane, 7-methylene mixed with 1-tetradecene, dimers and trimers, hydrogenated	ACTIVE
722503-68-6	Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	ACTIVE
68855-45-8	Phenol, dodecyl-, sulfurized, calcium salts	ACTIVE
92257-31-3	2-Naphthalenol, 1-((4-(phenylazo)phenyl)azo)-, ar-heptylar, ar, Methyl derivative	ACTIVE
1330-20-7	xylene	ACTIVE
100-41-4	ethylbenzene	ACTIVE

Hazardous Air Pollutants

1330-20-7	xylene
100-41-4	ethylbenzene

Proposition 65
Chemicals known to cause cancer:

100-41-4	ethylbenzene
----------	--------------

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 8)

Printing date 12/19/2023

Reviewed on 12/19/2023

Trade name: CROSS POWER 2T

(Contd. of page 7)

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National chemical directories** Components listed or exempted from listing:

· **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· **Department issuing SDS:** Abteilung Produktsicherheit

· **Date of preparation / last revision** 12/19/2023

· **Abbreviations and acronyms:**

Flammable Liquids 4: Flammable liquids – Category 4

Sensitization - Skin 1: Skin sensitisation – Category 1

Aspiration Hazard 1: Aspiration hazard – Category 1

· * **Data compared to the previous version altered.**

US