

1 Identification

- **Product identifier**
- **Trade name:** CHAINLUBE RACING
- **Application of the substance / the mixture**
Only for proper handling.
Chain lubricant
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MOTOREX AG
Bern-Zürich-Strasse 31, Postfach
CH-4901 Langenthal
Tel. +41 (0)62 919 75 75
www.motorex.com
- **Information department:** msds@motorex.com
- **Emergency telephone number:**
USA + Kanada: 1 800 424 9300 (Chemtrec Chemical Manufacturers Association, Arlington, VA 22209)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flammable Aerosols 1 H222 Extremely flammable aerosol.
Skin Irritation 2 H315 Causes skin irritation.
Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.
Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.
Aquatic Acute 3 H402 Harmful to aquatic life.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
n-hexane
Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
- **Hazard statements**
H222 Extremely flammable aerosol.
H315 Causes skin irritation.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

Trade name: CHAINLUBE RACING

(Contd. of page 1)

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P321 Specific treatment (see on this label).
- P331 Do NOT induce vomiting.
- P302+P352 If on skin: Wash with plenty of water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313 IF EXPOSED OR CONCERNED: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 4
Reactivity = 0

· **HMS-ratings (scale 0 - 4)**



Health = 1
Fire = 4
Reactivity = 3

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	<i>butane, pure</i> <hr style="border-top: 1px dashed black;"/> Flammable Gases 1, H220; Gases under Pressure - Compressed gas, H280	10-25%
--	--	--------

(Contd. on page 3)

Trade name: CHAINLUBE RACING

		(Contd. of page 2)
EC number: 920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flammable Liquids 2, H225; Aspiration Hazard 1, H304; Specific Target Organ Toxicity - Single Exposure 3, H336	≥10-<20%
	Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan Flammable Liquids 2, H225; Aspiration Hazard 1, H304; Aquatic Chronic 2, H411; Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336; Aquatic Acute 2, H401	≥10-<20%
EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Flammable Liquids 3, H226; Aspiration Hazard 1, H304; Specific Target Organ Toxicity - Single Exposure 3, H336	≥10-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane Flammable Gases 1, H220; Gases under Pressure - Compressed gas, H280	2.5-7.5%
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0	n-hexane Flammable Liquids 2, H225; Toxic to Reproduction 2, H361; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304; Aquatic Chronic 2, H411; Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336	0.25-1%
CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1	cyclohexane Flammable Liquids 2, H225; Aspiration Hazard 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336	≥0.1-<0.25%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Remove residues with soap and water.
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

Printing date 05/22/2024

Reviewed on 04/02/2024

Trade name: CHAINLUBE RACING

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

106-97-8	butane, pure	5500* ppm
9002-84-0	Polytetrafluoroethylene	12 mg/m ³
74-98-6	propane	5500* ppm
75-28-5	isobutane	5500* ppm
110-54-3	n-hexane	260 ppm
78-78-4	isopentane	3000* ppm
110-82-7	cyclohexane	300 ppm

- **PAC-2:**

106-97-8	butane, pure	17000** ppm
9002-84-0	Polytetrafluoroethylene	130 mg/m ³
74-98-6	propane	17000** ppm
75-28-5	isobutane	17000** ppm
110-54-3	n-hexane	2900* ppm
78-78-4	isopentane	33000*** ppm
110-82-7	cyclohexane	1700* ppm

- **PAC-3:**

106-97-8	butane, pure	53000*** ppm
9002-84-0	Polytetrafluoroethylene	790 mg/m ³
74-98-6	propane	33000*** ppm
75-28-5	isobutane	53000*** ppm
110-54-3	n-hexane	8600** ppm
78-78-4	isopentane	200000*** ppm
110-82-7	cyclohexane	10000** ppm

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

(Contd. on page 5)

Trade name: CHAINLUBE RACING

(Contd. of page 4)

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

The recommended storage temperature is (deg.C): ≤50°C

Keep receptacle tightly sealed.

· **Storage class:** 2 B

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

106-97-8 butane, pure

REL Long-term value: 1900 mg/m³, 800 ppm

TLV Short-term value: 1000 ppm
(EX)

74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppm

REL Long-term value: 1800 mg/m³, 1000 ppm

TLV see Appendix F Minimal oxygen content (D, EX)

110-54-3 n-hexane

PEL Long-term value: 1800 mg/m³, 500 ppm

REL Long-term value: 180 mg/m³, 50 ppm

TLV Long-term value: 50 ppm
Skin; BEI

110-82-7 cyclohexane

PEL Long-term value: 1050 mg/m³, 300 ppm

REL Long-term value: 1050 mg/m³, 300 ppm

TLV Long-term value: 100 ppm
BEI

· **Ingredients with biological limit values:**

110-54-3 n-hexane

BEI 0.5 mg/L

Medium: urine

Time: end of shift

Parameter: 2,5-Hexanedione without hydrolysis

(Contd. on page 6)

Trade name: CHAINLUBE RACING

(Contd. of page 5)

110-82-7 cyclohexane

BEI	NIC-50 mg/g creatinine
	Medium: -
	Time: end of shift at end of workweek
	Parameter: NIC-1.2-Cyclohexanediol (nonspecific)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Additional information about design of technical systems:** No further data; see section 7.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Not necessary if room is well-ventilated.
Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Not required.
- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Color:** white
- **Odor:** Solvent-like
- **Odor threshold:** Not determined.
- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** Not applicable, as aerosol.
- **Flammability (solid, gaseous):** Not applicable.
- **Explosion limits:**
- **Lower:** Not determined.

(Contd. on page 7)

Trade name: CHAINLUBE RACING

(Contd. of page 6)

· Upper:	Not determined.
· Flash point:	<-20 °C
· Decomposition temperature:	Not determined.
· pH-value:	Not determined.
· Viscosity:	
· Kinematic:	Not determined.
· Consistency	
· Dynamic:	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Vapor pressure:	Not determined.
· Vapor pressure:	
· Density at 20 °C:	0.73 g/cm ³ (ASTM D 4052)
· Relative density	Not determined.
· Vapor density	Not determined.
· Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Solvent separation test	
· VOC content:	71.74-≤73 %
· VOC (EU)	73.00 %
· Change in condition	
· Evaporation rate	Not applicable.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

106-97-8 butane, pure

Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)
	LC50 / 15 min	800,000 ppm (rat)
	LC50 / 2h	1,237 mg/l (mouse)
	LC50 / 2h	520,400-539,600 ppm (mouse)
	LC50 / 4h	658 mg/l (rat)
	NOAEC	4,000-16,000 ppm (rat)

(Contd. on page 8)

Trade name: CHAINLUBE RACING

(Contd. of page 7)

	NOAEC	7.2-21.4 mg/l (rat)
	LOAEC	21.6 mg/l (rat)
	LOAEC	12,000 ppm (rat)
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
Oral	LD50	8 ml/kg (rat)
Dermal	LD50	4 ml/kg (rat)
	LD50	2,800-3,100 mg/kg (rat)
Inhalative	LC50 / 4h	23.3 mg/l (rat)
	NOAEC	5.8-24.3 mg/l (rat)
Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclohexane, <5% n-Hexan		
Oral	LD50	8 ml/kg (rat)
Dermal	LD50	4 ml/kg (rat)
	LD50	2,800-3,100 mg/kg (rat)
Inhalative	LC50 / 4h	25.2 mg/l (rat)
	NOAEC	8.117-24.3 mg/l (rat)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics		
Oral	LD50	5,000-15,000 mg/kg (rat)
	NOAEL	1,000-5,000 mg/kg/24h (rat)
Dermal	LD50	2,000 mg/kg (rat)
		3,160-5,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	4.951-9.3 mg/l (rat)
	LC50 / 8h	41-4,467 ppm (rat)
	LC50 / 8h	5 mg/l (rat)
	NOAEL	200 ppm (rat)
	NOAEC	275-10,400 mg/m ³ (rat)
74-98-6 propane		
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)
	LC50 / 15 min	800,000 ppm (rat)
	LC50 / 2h	1,237 mg/l (mouse)
	LC50 / 2h	520,400-539,600 ppm (mouse)
	NOAEC	4,000-16,000 ppm (rat)
	NOAEC	7.214-21.394 mg/l (rat)
	LOAEC	21.64 mg/l (rat)
	LOAEC	12,000 ppm (rat)
110-82-7 cyclohexane		
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	32.88 mg/l (rat)
	LC50 / 4h	5,540 ppm (rat)
	NOAEC	500-2,000 ppm (mouse)
		500-7,000 ppm (rat)

- **on the skin:** Causes skin irritation.
- **Reproductive toxicity** Suspected of damaging fertility or the unborn child.
- **Specific target organ toxicity - single exposure** May cause drowsiness or dizziness.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

(Contd. on page 9)

Trade name: CHAINLUBE RACING

(Contd. of page 8)

· **Additional toxicological information:**

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

9002-84-0	Polytetrafluoroethylene	3
-----------	-------------------------	---

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

106-97-8 butane, pure

LC50	24.1-147.5 mg/l/96h (fish)
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

EC50	0.23 mg/l/21d (aquatic invertebrates)
EC50	0.64 mg/l/48h (aquatic invertebrates)
LL50	3-10 mg/l/96h (fish)
LL50	10-30 mg/l/72h (fish)
LL50	10-30 mg/l/48h (fish)
LL50	30-100 mg/l/24h (fish)
LL0	3 mg/l/96h (fish)
EL50	13 mg/l/96h (algae / cyanobacteria)
EL50	4.6-10 mg/l/48h (aquatic invertebrates)
	10-30 mg/l/48h (algae / cyanobacteria)
EL50	10-22 mg/l/24h (aquatic invertebrates)
	10-30 mg/l/24h (algae / cyanobacteria)
EL50	10-30 mg/l/72h (algae / cyanobacteria)
EL0	4.6 mg/l/48h (aquatic invertebrates)
EL0	10 mg/l/24h (aquatic invertebrates)
NOEC	0.17 mg/l/21d (aquatic invertebrates)
NOELR	0.574 mg/l/28d (fish)
NOELR	1 mg/l/21d (aquatic invertebrates)
NOELR	6.3 mg/l/96h (algae / cyanobacteria)
LOEC	0.32 mg/kg/28d (aquatic invertebrates)

Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan

EC50	0.23 mg/l/21d (aquatic invertebrates)
EC50	0.64 mg/l/48h (aquatic invertebrates)
LL50	11.4 mg/l/96h (fish)
LL50	15.8 mg/l/72h (fish)
LL0	5.1 mg/l/96h (fish)
EL50	3 mg/l/48h (aquatic invertebrates)
EL50	12 mg/l/24h (aquatic invertebrates)

(Contd. on page 10)

Trade name: CHAINLUBE RACING

(Contd. of page 9)

EL50	10-100 mg/l/72h (algae / cyanobacteria)
EL0	2 mg/l/48h (aquatic invertebrates)
EL0	10 mg/l/24h (aquatic invertebrates)
NOEC	0.17 mg/l/21d (aquatic invertebrates)
NOELR	2.045 mg/l/28d (fish)
NOELR	1 mg/l/21d (aquatic invertebrates)
LOEC	0.32 mg/kg/28d (aquatic invertebrates)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

LL50	1,000 mg/l/96h (fish)
LL50	1,000 mg/l/72h (fish)
LL50	1,000 mg/l/48h (fish)
LL50	1,000 mg/l/24h (fish)
LL0	100 mg/l/96h (fish)
EL50	1,000 mg/l/48h (aquatic invertebrates)
EL50	1,000 mg/l/24h (aquatic invertebrates)
EL50	1,000 mg/l/72h (algae / cyanobacteria)
EL0	1,000 mg/l/48h (aquatic invertebrates)
NOELR	0.131 mg/l/28d (fish)
NOELR	0.23 mg/l/21d (aquatic invertebrates)
NOELR	3-100 mg/l/72h (algae / cyanobacteria)

74-98-6 propane

LC50	24.11-147.54 mg/l/96h (fish)
LC50	14.22-69.43 mg/l/48h (aquatic invertebrates)
EC50	7.71-19.37 mg/l/96h (algae / cyanobacteria)

110-82-7 cyclohexane

LC50	4.53 mg/l/96h (fish)
EC50	0.9-2.4 mg/l/96h (aquatic invertebrates)
EC50	3.4-9.317 mg/l/72h (algae / cyanobacteria)
NOEC	0.9-0.94 mg/l/72h (algae / cyanobacteria)

· **Persistence and degradability** No further relevant information available.

· Bioaccumulative potential**106-97-8 butane, pure**

Partition coefficient	1.09-2.8 [---] (log Kow) (Bioaccumulation)
-----------------------	--

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Biologische Abbaubarkeit	98 % (28d) (Biodegradability) (OECD 301 F)
--------------------------	--

Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan

Biologische Abbaubarkeit	81 % (28d) (Biodegradability) (OECD 301 F)
--------------------------	--

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Biologische Abbaubarkeit	80 % (28d) (Bioaccumulation) (OECD 301 F)
--------------------------	---

74-98-6 propane

Partition coefficient	1.09-2.8 [---] (log Kow) (Bioaccumulation)
-----------------------	--

110-82-7 cyclohexane

Partition coefficient	3.44 [---] (log Kow) (Bioaccumulation)
Biologische Abbaubarkeit	77 % (28d) (Biodegradability) (OECD 301 F)

· **Mobility in soil** No further relevant information available.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

(Contd. on page 11)

Printing date 05/22/2024

Reviewed on 04/02/2024

Trade name: CHAINLUBE RACING

(Contd. of page 10)

- **vPvB:** Not applicable.
- **Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**

Water hazard class 2 (Self-classification according VwVwS, 17.05.1999): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Harmful to aquatic organisms

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 Contact waste processors for recycling information.
 Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.
- **Uncleaned packagings:**
- **Recommendation:**
 Disposal must be made according to official regulations.
 Discharged containers can contain flammable or explosive vapours.

14 Transport information

- | | |
|---|---|
| · UN-Number | |
| · DOT, ADR/RID/ADN, IMDG, IATA | UN1950 |
| · UN proper shipping name | |
| · DOT | Aerosols, flammable |
| · ADR/RID/ADN | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS |
| · IMDG | AEROSOLS, MARINE POLLUTANT |
| · IATA | AEROSOLS, flammable |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 2.1 Gases |
| · Label | 2.1 |
| <hr style="border-top: 1px dashed black;"/> | |
| · ADR/RID/ADN | |
| |  |
| · Class | 2 5F Gases |

(Contd. on page 12)

US

Trade name: CHAINLUBE RACING

(Contd. of page 11)

· **Label** 2.1

· **IMDG**



· **Class** 2.1 Gases
 · **Label** 2.1

· **IATA**



· **Class** 2.1 Gases
 · **Label** 2.1

· **Packing group**
 · **DOT, ADR/RID/ADN, IMDG, IATA** Void

· **Environmental hazards:** Product contains environmentally hazardous substances: Hydrocarbons C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane

· **Marine pollutant:** No
 Yes (DOT)
 Symbol (fish and tree)

· **Special marking (ADR/RID/ADN):** Symbol (fish and tree)

· **Special precautions for user** Warning: Gases

· **Hazard identification number (Kemler code):** -

· **EMS Number:** F-D,S-U

· **Stowage Code** SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
 SG69 For AEROSOLS with a maximum capacity of 1 litre:
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
 For AEROSOLS with a capacity above 1 litre:
 Segregation as for the appropriate subdivision of class 2.
 For WASTE AEROSOLS:
 Segregation as for the appropriate subdivision of class 2.

· **Segregation Code**

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Remarks:** Special marking with the symbol (fish and tree).

· **ADR/RID/ADN**

· **Excepted quantities (EQ)** Code: E0
 Not permitted as Excepted Quantity

(Contd. on page 13)

Trade name: CHAINLUBE RACING

(Contd. of page 12)

<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>1L Code: E0 Not permitted as Excepted Quantity</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS</p>

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

110-54-3	n-hexane
110-82-7	cyclohexane

- **TSCA (Toxic Substances Control Act):**

106-97-8	butane, pure	ACTIVE
9003-29-6	Polybuten (Isobutylen-/Buten-Copolymer)	ACTIVE
9002-84-0	Polytetrafluoroethylene	ACTIVE
74-98-6	propane	ACTIVE
75-28-5	isobutane	ACTIVE
110-54-3	n-hexane	ACTIVE
78-78-4	isopentane	ACTIVE
110-82-7	cyclohexane	ACTIVE
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	ACTIVE
110-25-8	(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	ACTIVE

- **Hazardous Air Pollutants**

110-54-3	n-hexane
----------	----------

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

110-54-3	n-hexane
----------	----------

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

110-54-3	n-hexane	II
110-82-7	cyclohexane	I

- **TLV (Threshold Limit Value)**

None of the ingredients is listed.

(Contd. on page 14)

Trade name: CHAINLUBE RACING

(Contd. of page 13)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· **Department issuing SDS:** Abteilung Produktsicherheit

· **Date of preparation / last revision** 05/22/2024 / -

· **Abbreviations and acronyms:**

Flammable Gases 1: Flammable gases – Category 1

Flammable Aerosols 1: Aerosols – Category 1

Gases under Pressure - Compressed gas: Gases under pressure – Compressed gas

Flammable Liquids 2: Flammable liquids – Category 2

Flammable Liquids 3: Flammable liquids – Category 3

Skin Irritation 2: Skin corrosion/irritation – Category 2

Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3