

Marca	Royal Enfield
Modelo	Interceptor (2018-)
Tipo	Interceptor 650 E5 2021 -

Motor/transmisión

Cantidad de llenado:	Capacidad 3,9 litro (Llenado en seco) Capacidad 3,1 litro (Llenado tras el mantenimiento)
Uso:	Primer servicio
Intervalos:	Cambiar cada 500 km/ 6 semana
Productos:	➤ POWER SYNT 4T SAE 10W/50 MA2 ➤ FORMULA 4T SAE 15W/50 MA2 Otros productos ➤ FORMULA 4T SAE 10W/50 MA2
Uso:	Normal
Intervalos:	Cambiar cada 7500 km/ 12 meses
Productos:	➤ POWER SYNT 4T SAE 10W/50 MA2 ➤ FORMULA 4T SAE 15W/50 MA2 Otros productos ➤ FORMULA 4T SAE 10W/50 MA2

Sistema de frenos

Cantidad de llenado:	Capacidad 50 cm3 (Delante) Capacidad 100 cm3 (Atrás)
Uso:	Normal
Intervalos:	Cambiar cada 20000 km/ 24 meses Comprobar cada 5000 km/ 12 meses
Productos:	➤ BRAKE FLUID DOT 4

Horquilla delantera

Cantidad de llenado:	Capacidad 473 cm3 (cada pata)
Uso:	Normal
Intervalos:	Cambiar cada 60000 km Comprobar cada 5000 km

Productos: > Bitte kontaktieren Sie unseren technischen Kundendienst Tel. +41 62 919 75 75

MOTOREX-BUCHER GROUP AG
Bern-Zürich-Strasse 31 • Postfach • 4901 Langenthal, Schweiz
Tel. +41 62 919 75 75 • Fax. +41 62 919 75 95
info@motorex.com

All information given in the oil guide is based on the general experience and knowledge of the MOTOREX-Bucher Group AG in the development and production of lubricants and corresponds to our present state of knowledge. The mode of operation of our products depends on various factors, in particular on the specific application purpose, the application of the products, the operating conditions, the component pre-treatment, possible dirt accumulation from the outside, etc. For this reason, it is not possible to use our products in general. The data represent general, non-binding guidelines. On the other hand, they do not in any way include an assurance of properties or a guarantee for the suitability of the product for the individual case. Before using our products, we therefore recommend that you have an individual consultation with the MOTOREX-Bucher Group AG contact persons about the operating conditions in the application and the performance characteristics of the products. Our products may not be used in aerospace vehicles or parts thereof. This does not apply if the products are removed before installation of components in an aerospace vehicle.

It is incumbent upon the user to test the products in the intended application for their functional safety and to use them with the necessary care. Our products are continuously being developed further. For this reason, we reserve the right to change the product range, the products and their manufacturing processes as well as all information, e. g. in the oil guide, at any time and without prior notice. All previous publications lose their validity with the publication of this publication. Duplication of any kind and form requires the prior written consent of the MOTOREX-Bucher Group AG.

© MOTOREX-Bucher Group AG. All rights reserved.